

Metallic 90 Degree / Right Angle Adaptors

Ex db : Ex eb : Ex nR : Ex ta : IP66 : IP68 : Class I Div 1 : AEx db : AEx eb : AEx ta




PRODUCT TYPE ARMR & ARFR



PRODUCT DESCRIPTION

"ARMR" & "ARFR" Series Dual Certified Right Angled Adaptors are designed to protect cables when installed in confined spaces where the cable may otherwise be subject to excessive bending and / or stress. The series is available with Male/Female or Female/Female connection threads. They are approved for Ex db, Ex eb, Ex ta and Ex nR methods of explosion protection whilst maintaining IP66, IP68 for IEC type applications and Class I Division 1, and Type 4X/6P for NEC/CEC type applications. All external parallel threads are fitted with a nitrile O-ring as standard.



COMPLIANCE STANDARDS:

EN 60079-0, EN 60079-1, EN 60079-7, EN 60079-15, EN 60079-31
IEC 60079-0, IEC 60079-1, IEC 60079-7, IEC 60079-15, IEC 60079-31 & 60529
C22.2 (see certificate), UL514B, UL1203, ANSI/UL 60079-0/1/7, ISA 60079-31, UL 50E

CERTIFICATION:	UKEX	I M2 II 1D 2G Ex db I Mb / Ex db IIC Gb / Ex eb I Mb / Ex eb IIC Gb / Ex ta IIIC Da II 3G Ex nR IIC Gc
	ATEX	I M2 II 1D 2G Ex db I Mb / Ex db IIC Gb / Ex eb I Mb / Ex eb IIC Gb / Ex ta IIIC Da II 3G Ex nR IIC Gc
	IECEX	Ex db I Mb / Ex db IIC Gb / Ex eb I Mb / Ex eb IIC Gb / Ex nR IIC Gc / Ex ta IIIC Da
	CEC - Canada	Ex db IIC Gb / Ex eb IIC Gb / Ex ta IIIC Da Class I Division 1, Groups A, B, C & D Class II Division 1, Groups E, F & G Class III, Type 4X/6P
	NEC - USA	Class I Zone 1 AEx db IIC Gb / AEx eb IIC Gb / Class II Zone 20 AEx ta IIIC Da Class I Division 1, Groups A, B, C & D Class II Division 1, Groups E, F & G Class III, Type 4X/6P
	EAC	PB Ex db I Mb U / 1Ex db IIC Gb U / PB Ex eb I Mb U / 1Ex eb II Gb U / 2Ex nR II Gc U Ex ta IIIC Da U
	INMETRO - Brazil	Ex db I Mb / Ex db IIC Gb / Ex eb I Mb / Ex eb IIC Gb / Ex nR IIC Gc / Ex ta IIIC Da
	CCC - China	Ex db I Mb / Ex db IIC Gb / Ex eb I Mb / Ex eb IIC Gb / Ex nR IIC Gc / Ex ta IIIC Da
	UKRAINE	I M2 Ex db I Mb / Ex eb I Mb / II 2GD Ex db IIC Gb / Ex eb IIC Gb / Ex ta IIIC Da II 3G Ex nR IIC Gc
	CCoE - India	Ex db I Mb / Ex db IIC Gb / Ex eb I Mb / Ex eb IIC Gb / Ex nR IIC Gc
ABS	Specified ABS Rules	
LLOYD'S	Ex db I Mb / Ex db IIC Gb / Ex eb I Mb / Ex eb IIC Gb / Ex nR IIC Gc / Ex ta IIIC Da	
DNV	Ex db I Mb / Ex db IIC Gb / Ex eb I Mb / Ex eb IIC Gb / Ex nR IIC Gc / Ex ta IIIC Da	

CERTIFICATION No:	UKEX	CML 21UKEX1040U & CML 21UKEX4041U
	ATEX	CML 19ATEX1091U & CML 19ATEX4093U
	IECEX	IECEX CML 19.0023U
	CEC - Canada	CSA 2310046
	NEC - USA	CSA 2310046
	EAC	RU C-GB.AXK58.B.051063/24
	INMETRO - Brazil	NCC 13.2190 U
	CCC - China	2021312313000375
	UKRAINE	CL 18.0319 X
	CCoE - India	PESO P494321/3 & P494321/12
ABS	20-LD1944057-PDA	
LLOYD'S	LR2124442TA	
DNV	TAE00004XK	

EXAMPLE PART NUMBERING: ARMR1BF/NP/M20/M20

AR	Thread converting Adaptor
MR	Male/Female Right Angled (MR) - Female/Female Right Angled (FR)
1	No IP O-ring (0) - Nitrile (1) - Silicone (3) (Only available on ARMR)
B	Brass (B) - Stainless Steel (S) - Aluminium (A)
F	Multiple Certification
K-V-H	Locknut & Nylon (K), Fibre (V) or PTFE (H) IP Washer
T	Including Earth Tag
S	Including Serrated Washer
1	Quantity per kit
NP	Nickel Plated
M20	Male Entry Thread
M20	Female Entry Thread

ARFR part numbers will always contain the "0" as this product cannot be fitted with O-rings.

IP RATING:	IP66, IP68 (100 metres for 7 days) & Type 4X/6P
OPERATING TEMPERATURE:	O-ring - None -100°C to +400°C O-ring - Nitrile -30°C to +100°C O-ring - Silicone -60°C to +200°C
MATERIALS:	Brass, Stainless Steel or Aluminium
PLATING:	Electroless Nickel

**ALSO AVAILABLE IN 30 DEGREE AND 45 DEGREE CONFIGURATIONS
APPROVALS MAY VARY PLEASE CONTACT US FOR DETAILS**

ADAPTOR SELECTION TABLE (ALL DIMENSIONS IN mm)

Metric					NPT				
Size	Bore	Height	Length	Width	Size	Bore	Height	Length	Width
M16 x M16	10.0	38.1	27.0	25.4	3/8" x 3/8"	10	38.1	27	25.4
M20 x M20	14.0	38.1	27.0	25.4	1/2" x 1/2"	14.1	43	27	25.4
M25 x M25	18.0	44.5	37.0	31.8	3/4" x 3/4"	19	51	37	31.75
M32 x M32	24.0	50.8	45.0	38.1	1" x 1"	25	62	45	38.1
M40 x M40	32.0	63.5	52.0	50.8	1 1/4" x 1 1/4"	32	75	52	50.8
M50 x M50	41.0	72.0	67.0	60.0	1 1/2" x 1 1/2"	38	83.5	67	60
M63 x M63	53.0	90.0	83.0	75.0	2" x 2"	49	100	83	75
M75 x M75	64.0	102.0	94.0	88.0	2 1/2" x 2 1/2"	60	125	94	88
M80 x M80	69.0	120.0	110.0	100.0	3" x 3"	75	148	120	110
M85 x M85	73.0	125.0	115.0	110.0	3 1/2" x 3 1/2"	88	155	125	120
M90 x M90	78.0	130.0	120.0	110.0					
M100 x M100	88.0	140.0	125.0	130.0					

NOTES

- Assembly instructions must be read prior to installation and adhered to in full.
- For Ex db applications female threads must comply with clause 5.3 of IEC 60079-1.
- For Ex nR applications parallel entry threads must be installed with a suitable entry thread seal.
- Where applicable, the standard O-ring material is nitrile. Other options are available upon request.
- Aluminium versions are not suitable for Group I Mining applications.
- Only products with Metric and NPT threads are marked with CSA approval.
- Brass products are not marked or intended to be used in Class I Division 1 installations.
- Peppers supply products with parallel entry threads that conform to the flameproof threaded joint

- requirements of IEC/EN 60079-1 and other equivalent standards. We usually incorporate a thread run out according to the general machining techniques and will not have a full form thread for the entire length. Peppers Cable Glands Limited will not be held responsible for clients' installations where this has not been taken into account.
- Where approval in addition to UKEX, ATEX, IECEX and CSA is required, this must be clearly requested at time of enquiry / order.