

CERTIFICATE OF COMPLIANCE

Certificate Number E340660
Report Reference E340660-20200514
Issue Date 2020-MAY-18

Issued to: PEPPERS CABLE GLANDS LTD
STANHOPE RD, CAMBERLEY
GU15 3BT UNITED KINGDOM

**This certificate confirms that
representative samples of**

COMPONENT - CONDUIT FITTINGS FOR USE IN ZONE
CLASSIFIED HAZARDOUS LOCATIONS

See Addendum Page

Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety:
Additional Information:


See Addendum Page

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E340660
Report Reference E340660-20200514
Issue Date 2020-MAY-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USR - Breather/Drain Fittings Type ACDP, followed by 0, 1, 3, followed by B, S or A, followed by E, followed by 00, NP, ZP or AN, followed by M12, M16, M20, M25, M32, 1/4", 3/8", 1/2" or 3/4", followed by X or S, for use in Class I, Zone 1, AEx eb IIC Gb, Hazardous Locations.

Breather/Drain Fittings Type ACDP, followed by 1, 3, followed by B, S or A, followed by E, followed by 00, NP, ZP or AN, followed by M12, M16, M20, M25, M32, 1/4", 3/8", 1/2" or 3/4", followed by X or S, for use in Zone 20 AEx ta IIIC Da, Hazardous Locations.


Standards:

UL 60079-0 - EXPLOSIVE ATMOSPHERES - PART 0: EQUIPMENT - GENERAL REQUIREMENTS

UL 60079-7 - STANDARD FOR EXPLOSIVE ATMOSPHERES - PART 7: EQUIPMENT PROTECTION BY INCREASED SAFETY "E"

UL 60079-31 Explosive Atmospheres - Part 31: Equipment Dust Ignition Protection by Enclosure "t"

UL 514B - Conduit, Tubing, and Cable Fittings



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

