

PRODUCT TYPE CR-D

Single Seal Gland for Armoured Cable featuring "CROCLOCK"[®]

Ex db : Ex eb : Ex nR : Ex ta : IP66 : IP68 : Class I Zone 1 : AEx eb : AEx ta



PRODUCT DESCRIPTION

"CR-D" type glands are certified Flameproof Ex db, Increased Safety Ex eb, Restricted Breathing Ex nR and Dust Protected Ex ta. They are suitable for use in Zone 1 and 2 for Gas Groups IIA, IIB and IIC and additionally for use in Zones 20, 21 and 22 for Dust Groups IIIA, IIIB and IIIC. Also certified for Zone and Division installations for use with Marine Shipboard and Tray Cables under the NEC and CEC. They provide a controlled Ex db & IP displacement seal on the cable inner sheath minimising damage to cables that exhibit "cold flow" characteristics and "CROCLOCK"[®], a unique non reversible multi clamping system for wire, braid and tape armoured cables. The gland maintains IP66 & IP68 to 50 metres. It is supplied with an IP O-ring seal as standard on metric entry threads. Options are available for use with lead sheath, LSOH cables and extreme temperature applications.

COMPLIANCE STANDARDS:

EN 60079-0, EN 60079-1, EN 60079-7, EN 60079-15, EN 60079-31
IEC 60079-0, IEC 60079-1, IEC 60079-7, IEC 60079-31 & IEC 60529
C22.2 (see certificate), CAN/CSA 60079-0/1/7/31
UL514B, UL1203, UL2225, UL50E, ANSI/UL 60079-0/7, ISA 60079-31

EXAMPLE PART NUMBERING: CR-DIBCK1/NP/20/M20

CR	Gland featuring "CROCLOCK" [®] , single orientation clamping
D	Inner Sheath Seal Only
1	Neoprene Seal (1) - Silicone Seal (3)
B	Brass (B) - Stainless Steel (S)
C	PVC Shroud (C) - PCP Shroud (P) - LSOH Silicone Shroud (3)
K-V-H	Locknut, Earth Tag & Nylon (K), Fibre (V) or PTFE (H) IP Washer
S	Including Serrated Washer
1	Quantity per kit
NP	Nickel Plated
20	Gland shell size
M20	M20 x 1.5 Male Entry Thread

OPTIONAL ACCESSORIES:

LOCKNUT	Brass (ACBLN) / Stainless Steel (ACSLN)
EARTH TAG	Brass (ACBET) / Stainless Steel (ACSET)
IP WASHERS	Nylon (ACNSW) / Fibre (ACFSW) / PTFE (ACPSW)
SERRATED WASHERS	Stainless Steel (ACSSW)
SHROUDS	PVC (ACSPVC) / PCP (ACSPCP) / LSOH Silicone (ACSSIO)

IP RATING:	IP66 & IP68 (50 metres - 7 Days), Type 4X & DTS01:1991
OPERATING TEMP:	Neoprene Seals -35°C to +90°C Silicone Seals -60°C to +180°C
MATERIALS:	Brass or Stainless Steel
PLATING:	Electroless Nickel

CERTIFICATION:

UKEX	II 1D 2G Ex db IIC Gb / Ex eb IIC Gb / Ex ta IIIC Da II 3G Ex nR IIC Gc
ATEX	II 1D 2G Ex db IIC Gb / Ex eb IIC Gb / Ex ta IIIC Da II 3G Ex nR IIC Gc
IECEX	Ex db IIC Gb / Ex eb IIC Gb / Ex nR IIC Gc / Ex ta IIIC Da
CEC - Canada	Ex db IIC Gb / Ex eb IIC Gb / Ex ta IIIC Da Class II Group E, F & G Class III, Type 4X
NEC - USA	Class I Zone 1 AEx eb IIC Gb / Zone 20 AEx ta IIIC Da Class II Group E, F & G Class III, Type 4X
EAC	1Ex db IIC Gb X / 1Ex eb IIC Gb X / 2Ex nR IIC Gc X / Ex ta IIIC Da X
INMETRO - Brazil	Ex db IIC Gb / Ex eb IIC Gb / Ex nR IIC Gc / Ex ta IIIC Da
CCC - China	Ex db IIC Gb / Ex eb IIC Gb / Ex nR IIC Gc / Ex ta IIIC Da
UKRAINE	II 2G Ex db IIC Gb / II 2G Ex eb IIC Gb / II 3G Ex nR IIC Gc / II 1D Ex ta IIIC Da
CcOE - India	Ex db IIC Gb / Ex eb IIC Gb / Ex nR IIC Gc / Ex ta IIIC Da
ECAS-Ex	Ex db IIC Gb / Ex eb IIC Gb / Ex nR IIC Gc / Ex ta IIIC Da
KCS-Korea	Ex d IIC / Ex e IIC
ABS	Specified ABS Rules
LLOYD'S	Ex db IIC Gb / Ex eb IIC Gb / Ex nR IIC Gc / Ex ta IIIC Da
DNV	Ex db IIC Gb / Ex eb IIC Gb / Ex nR IIC Gc / Ex ta IIIC Da

CERTIFICATION NO:

UKEX	CML 21UKEX1030X & CML 21UKEX4043X
ATEX	CML 19ATEX1348X & CML 19ATEX4109X
IECEX	IECEX CML 19.0106X
CEC - Canada	CSA 1356011
NEC - USA	CSA 1356011
EAC	RU C-GB.AX58.B.05106/24
INMETRO - Brazil	NCC 13.2185 X
CCC - China	2021312313000409
UKRAINE	CLJ 18.0326 X
CcOE - India	PESO P494321/8 & P494321/13
ECAS-Ex	25-06-153223/E25-06-159811/NB0007
KCS - Korea	15-GA4BO-0669X & 15-GA4BO-0670X
ABS	25-0158110-PDA
LLOYD'S	LR2124442TA
DNV	TAE00004XK

CABLE GLAND SELECTION TABLE (ALL DIMENSIONS IN mm)

Gland size	Entry Thread Size		Metric Thread Length [B]	Cable Acceptance Details			Armour Acceptance Range	Nominal Protusion Length [L]	Dimensions/Weight (Metric Versions)			Shroud Size (Metric)
	Metric	NPT		Inner Sheath [C]		Outer Sheath [D]			Across Flats [A]	Across Corners	Weight (Kgs)	
16	M20 x 1.5	1/2" or 3/4"	16	3.4	8.4	13.5	0.15-1.25	78	25.4	28.0	0.178	EL24*
20S	M20 x 1.5	1/2" or 3/4"	16	7.2	11.7	16.0	0.15-1.25	78	25.4	28.0	0.173	EL24*
20	M20 x 1.5	1/2" or 3/4"	16	9.4	14.0	21.1	0.15-1.25	78	30.0	33.0	0.233	EL30
25	M25 x 1.5	3/4" or 1"	16	13.5	20.0	27.4	0.15-1.60	90	37.6	41.4	0.416	EL38
32	M32 x 1.5	1" or 1 1/4"	16	19.5	26.3	34.0	0.15-2.00	105	46.0	50.6	0.772	EL46
40	M40 x 1.5	1 1/4" or 1 1/2"	16	23.0	32.2	40.6	0.20-2.00	113	55.0	60.5	1.093	EL55
50S	M50 x 1.5	1 1/2" or 2"	16	28.1	38.2	46.7	0.20-2.50	125	65.0	71.5	1.255	EL65
50	M50 x 1.5	2"	16	33.1	44.1	53.2	0.30-2.50	125	65.0	71.5	1.400	EL65
63S	M63 x 1.5	2" or 2 1/2"	19	39.2	50.1	59.5	0.30-2.50	125	80.0	88.0	2.550	EL80
63	M63 x 1.5	2 1/2"	19	46.7	56.0	65.8	0.30-2.50	125	80.0	88.0	2.104	EL80
75S	M75 x 1.5	2 1/2" or 3"	19	52.1	62.0	72.2	0.30-2.50	131	90.0	99.0	2.916	EL90
75	M75 x 1.5	3"	19	58.0	68.0	78.0	0.30-2.50	131	90.0	99.0	2.315	EL90
80	M80 x 2.0	3" or 3 1/2"	25	62.2	72.0	84.0	0.45-3.15	170	90.0	115.2	4.953	EL104
85	M85 x 2.0	3" or 3 1/2"	25	69.0	78.0	90.0	0.45-3.15	170	104.0	115.2	4.070	EL104
90	M90 x 2.0	3 1/2" or 4"	25	74.0	84.0	96.0	0.45-3.15	170	114.0	125.7	5.129	EL114
100	M100 x 2.0	3 1/2" or 4"	25	82.0	90.0	102.0	0.45-3.15	170	114.0	125.7	4.362	EL114
110	M110 x 2.0	4"	25	92.0	102.0	117.0	0.45-3.15	165	135.0	148.5	7.327	-

NOTES

- Gland size does not necessarily equate to the entry thread size.
- The IP O-ring seal is only available on metric entry threads. IP washers can be supplied for tapered entry threads.
- Dimensions (A) & (B) may differ for glands with non metric entry threads. Please refer to our "Thread Reference Tables" for specific dimensions.
- Assembly instructions must be read prior to installation and adhered to in full.
- Peppers supply products with parallel entry threads that conform to the flameproof threaded joint requirements of IEC/EN 60079-1 and other equivalent standards. We usually incorporate a thread run out according to general machining techniques and parts will not have a full form thread for the entire length. Peppers Cable Glands Limited will not be held responsible for

- clients' installations where this has not been taken into account.
- When selecting IP Washer & Shroud material for use with glands, please be aware of the accessories temperature range to ensure they are suitable for the intended installation.
- Where approval in addition to UKEX, ATEX, IECEX and CSA is required, this must be clearly requested at time of enquiry / order.
- * For gland sizes 16 and 20S when used with 3/4" NPT entry thread an EL30 shroud would be required.